

Laserliner®

TireCheck




Digital tyre tester for checking tyre pressure and tread depth

Rev.1214



- For checking **tyre pressure** in psi and bar
- **Digital gauge** for checking tread depth
- **Auto Power-off:** the device switches off automatically when left idle for 90 seconds.
- **LCD Backlight:** Illuminated LC display
- Easy to use



Illuminated LC display



Tread depth measurement with digital display

TECHNICAL DATA

TYRE PRESSURE MEASUREMENT

Measurement range:
0.21 - 6.85 bar max.
(3.0 - 99.5 psi max.)
Accuracy: $\pm 0,1$ bar / $\pm 1,5$ psi
Resolution: 0,03 bar / 0,5 psi

CHECKING TREAD DEPTH

Measurement range: 0 - 15,8 mm
Accuracy: $\pm 0,5$ mm
Resolution: 0,1 mm

AUTO POWER OFF 90 seconds

STORAGE TEMPERATURE -10 °C ... 55 °C

OPERATING TEMPERATURE 0 ... 50 °C

RELATIVE HUMIDITY

20% rH ... 80% rH, no condensation

POWER SUPPLY

2 x LR44 button cell, 1.5 V

DIMENSIONS (W x H x D)

35 x 131 x 57 mm

WEIGHT (incl. batteries)

74 g



TireCheck
+ batteries

Packing dimension (W x H x D)
110 x 235 x 50 mm

| ARTICLE | ARTICLE NO | EAN-CODE | PU |
|-----------|------------|-----------------|----|
| TireCheck | 082.180A | 4 021563 690077 | 5 |

